

MINS CO., LTD.

2F, No.11 Nanyuan 2nd Rd., Jhongli City, Taoyuan County
320, Taiwan R.O.C.
Tel : 886-3-433-1575 Fax : 886-3-4613911
<http://www.yaba.com.tw> E-mail : yabamaster@yaba.com.tw

4CH H.264 STANDALONE DVR



- H.264 Video Compression Technology
- Highly improves video quality for live, recording, and network
- Recording file size is minimized for longest recording time
- Lower bit rate required for fastest network transfer
- VGA interface built-in
- Multiplex
- Supports USB flash drive and network backup
- Remote Surveillance
- Intelligent Motion Trigger Recording
- Customizable security settings are achieved with the advanced motion detection, the scheduled motion detection recording, and the quick search function
- Supports 1 audio-in, 1 audio-out to record sounds
- Supports multi-language OSD
- Supports SATA HDD (SATA interface built-in)
- Supports IR remote control
- System auto recovery after power failure



MINS CO., LTD.

2F.,No.11 Nanyuan 2nd Rd.,Jhongli City, Taoyuan County
320,Taiwan R.O.C..
Tel : 886-3-433-1575 Fax : 886-3-4613911
<http://www.yaba.com.tw> E-mail : yabamaster@yaba.com.tw

OPERATION SYSTEM			Linux
Video	Video System	NTSC/PAL Switch Selectable	
	Input	BCNx4,1.0Vp-p, 75 ohm	
	Outputs Main	BCNx1,1.0Vp-p, 75 ohm	
	VGA Output	Optional	
Audio	Input	1CH.RCA	
	Output	1CH.RCA	
Control	Mouse	USB Mouse	
	IR Controller	Yes	
Storage	Bulid in Interface	SATA Hard Diskx1	
Display	Division	1, 4	
	Zoom	2x	
Recording	Compression	H.264	
	Recording mode	Manual, Schedule, Event, Holiday	
	Resolution	NTSC	120fps (720x480), 120fps (720x240),120 fps (360x240)
		PAL	100fps (720x576) 100fps (720x288) 100fps (360x288)
	Frame Rate	NTSC	120fps (720x480), 120fps (720x240),120 fps (360x240)
		PAL	100fps (720x576) 100fps (720x288) 100fps (360x288)
	Quality	Highest, High, Normal, Low, Lowest	
	Motion Detection	Sensitivity:15Level, 16x12 Grid	
	Alarm	Pre-Alarm	16MB
		Post-Alarm	16MB
	Speed	Normal,REW&FF(2x/4x/8x/16x/32x/64x), Pause	
Playback	Search Method	Event, Calendar	
Communication	Remote Software	AP, IE Browser	
	Remote Operation	Virtual DVR-Same As Local OSD	
	Network Service	TCP/IP, HTTP, DHCP, ADSL, LAN, DDNS	
	GUI Interface	Supported	
Back up	External	USB2.0	
	Network	Yes	
	Backup File	H.264 compression / AP	
General	Unit Dimension	300x 175x 46 mm	
	Recover	Watchdog	
	Operation Temperature	-5°C~40°C	
	Power Consumption	DC12V, 5A	